



CMR 15

MF (13.56 MHZ) CARD READER

Makim CMR 15 Mf (13.56 Mhz) is a card reader with communication option of TCP/IP (Ethernet) and is suitable for applications for indoor with its stylish case.





Makim CMR 15 Mf (13.56 Mhz) Card Reader is used for access control applications with its 5.000 user capacity and stylish design. It is a card reader with its 200.000 log capacity and it has door-turnstile opening function via relay (dry contact). CMR 15 provides fast operation with a reading speed under 20ms for 5.000 user.

TCP/IP communication provides access to all log information, entryexit data, employee-based authorization, and all reports like daily, weekly and monthly reporting. CMR 15 can also be connected to panel through wiegand in/out and RS485 connection is available.

The device works with 12 V power and it gives sound alarm with its built-in buzzer in every transaction. With the 1.6 TFT color screen, you can follow the operations on the screen. When you read the card, the card id appears on the reader screen if it has been saved. With all these features, CMR 15 Mf (13.56 Mhz) Card Reader is suitable for not only small business centers, accommodation places or buildings but it also suitable for big factories, storage rooms, banks, prisons and similar industrial and commercial locations.

Card Capacity	5.000
Log Capacity	200.000
Card	Mf (13.56 Mhz)
Communication	TCP/IP, RS 485, Wiegand In/Out
Relay	Yes, Dry Contact
Screen	Colorful
Operating System	32 Bit CPU
Dimensions	48 x 38 x 138 mm
Operation Voltage	12 V DC