D 45

## PROXIMITY FACE RECOGNITION TERMINAL

D 45 proximity face recognition terminal is a stylishly designed access control terminal with a high-screen memory and advanced algorithm.

- Advanced Face Recognition Technology
- High Performance
- Stylish Design
- Easy Installation
- Turnstile Door Opening
- Communication
- Quick Match

D 45 proximity face recognition terminal is a stylishly designed access control terminal with a high-screen memory and advanced algorithm. D 45 face recognition terminal, face recognition + proximity card pass options has relay reader with turnstile and door opening feature are used in accordance with the indoor areas.

The reader has 2.000 face recognition, 2.000 card capacity and the log capacity of the reader is 200.000. Users can easily manage the data with a TCP / IP connection with the software, and with the USB connection all 200.000 log movements can be easily received from the device. All reports such as log information, entry-exit information, person-based authorization, daily, weekly, and monthly reports can be received from the reader, which communicates directly with the TCP / IP communication portal. At the same time, in the D 45 colour display face recognition terminal, which can communicate with wiegand in/out and USB output; If the user information is registered on the system, it can be seen on the display when you read your face or card. The device works with 12 V and it gives sound alarm with its buzzer in every transaction.

From the device menu, access can be done, personnel authorization can be managed. Logs can transfered with USB.

With these features, the D 45 face recognition terminal is an ideal product not only for small workplaces, homes, apartments, site management, but also for access controls for commercial and industrial applications such as factories, warehouses, laboratories, banks, prisons.

Face Capacity	2.000
Card Capacity	2.000
Log Capacity	200.000
Card	Proximity
Communication	TCP/IP, USB, Wiegand In/ Out
Relay	Yes
Display	4 inch, 480*800 LCD
Operating Voltage	12 V DC